

Transparente c/ Espiral Laranja

Serviço Pesado

Indicada para serviços pesados de sucção e descarga, tais como Irrigação Agrícola e Construção Civil.

Temperatura de Trabalho: +5°C ~ +50°C (PVC).



DIÂMETRO NOMINAL	DIÂMETRO INTERNO	DIÂMETRO EXTERNO	PRESSÃO DE TRABALHO		PRESSÃO DE RUPTURA		VÁCUO	RAIO DE CURVATURA Trabalho - Mínimo	LANÇE
			25°C kgf/cm ²	25°C lbf/pol ²	25°C kgf/cm ²	25°C lbf/pol ²			
pol.	mm	mm					25°C mmHg	25°C mm	m
2"	50,0	59,5	7,3	104	22,0	313	760	700	25 / 50
2.1/2"	62,5	73,0	7,3	104	22,0	313	760	800	25 / 50
3"	74,5	86,0	6,7	95	20,0	284	760	900	25 / 50
4"	101,2	115,0	6,0	85	18,0	256	760	1.500	25 / 50
5"	127,0	141,0	4,7	66	14,0	199	760	2.500	15 / 30
6"	150,5	166,0	4,0	57	12,0	171	760	2.750	15 / 30
8"	204,0	224,4	3,3	47	10,0	142	760	4.500	15 / 30
10"	255,0	275,0	2,8	40	8,4	119	750	7.000	10
* 12"	304,5	328,5	2,7	38	8,0	114	750	10.000	10

*Fornecimento sob consulta.

Transparente con Espiral Naranja

Servicio Pesado

Para servicios pesados de succión y descarga, como Riego Agrícola y Construcción Civil.

Temperatura del Trabajo: +5°C ~ +50°C (PVC).



DIÂMETRO NOMINAL	DIÂMETRO INTERIOR	DIÂMETRO EXTERIOR	PRESIÓN DEL TRABAJO		PRESIÓN DEL RUPTURA		VACIO	RADIO DE CURVATURA Trabajo - Mínimo	LARGO
			25°C kgf/cm ²	25°C lbf/pol ²	25°C kgf/cm ²	25°C lbf/pol ²			
pul.	mm	mm					25°C mmHg	25°C mm	m
2"	50,0	59,5	7,3	104	22,0	313	760	700	25 / 50
2.1/2"	62,5	73,0	7,3	104	22,0	313	760	800	25 / 50
3"	74,5	86,0	6,7	95	20,0	284	760	900	25 / 50
4"	101,2	115,0	6,0	85	18,0	256	760	1.500	25 / 50
5"	127,0	141,0	4,7	66	14,0	199	760	2.500	15 / 30
6"	150,5	166,0	4,0	57	12,0	171	760	2.750	15 / 30
8"	204,0	224,4	3,3	47	10,0	142	760	4.500	15 / 30
10"	255,0	275,0	2,8	40	8,4	119	750	7.000	10
12"	304,5	328,5	2,7	38	8,0	114	750	10.000	10

Transparent with Orange Spiral

Heavy Jobs

Recommended for heavy jobs of suction or discharge, such as Agricultural Irrigation and Civil Construction.

Work temperature: +5°C ~ +50°C (PVC).



NOMINAL DIAMETER	INTERNAL DIAMETER	EXTERNAL DIAMETER	WORK PRESSURE		BURST PRESSURE		VACUUM	BEND RADIUS Working - minimum	LENGTH
			25°C kgf/cm ²	25°C psi	25°C kgf/cm ²	25°C psi			
inches	mm	mm					25°C mmHg	25°C mm	m
2"	50,0	59,5	7,3	104	22,0	313	760	700	25 / 50
2.1/2"	62,5	73,0	7,3	104	22,0	313	760	800	25 / 50
3"	74,5	86,0	6,7	95	20,0	284	760	900	25 / 50
4"	101,2	115,0	6,0	85	18,0	256	760	1.500	25 / 50
5"	127,0	141,0	4,7	66	14,0	199	760	2.500	15 / 30
6"	150,5	166,0	4,0	57	12,0	171	760	2.750	15 / 30
8"	204,0	224,4	3,3	47	10,0	142	760	4.500	15 / 30
10"	255,0	275,0	2,8	40	8,4	119	750	7.000	10
12"	304,5	328,5	2,7	38	8,0	114	750	10.000	10