

KPG

Transparente c/ Espiral Laranja

Serviço Pesado

Indicada para serviços pesados de sucção e descarga na Irrigação Agrícola e Construção Civil.
Temperatura de Trabalho: +5°C ~ +50°C (PVC).



DIÂMETRO NOMINAL	DIÂMETRO INTERNO	DIÂMETRO EXTERNO	PRESSÃO DE TRABALHO		PRESSÃO DE RUPTURA		VÁCUO	RAIO DE CURVATURA Trabalho - Mínimo	LANCE
pol.	mm	mm	25°C		25°C		25°C	25°C	m
			kgf/cm ²	lbf/pol ²	kgf/cm ²	lbf/pol ²	mmHg	mm	
5"	127,0	141,5	5,0	71	15,0	213	760	2.550	15 / 30
6"	152,4	169,0	4,6	65	14,0	199	760	2.800	15 / 30

Transparente con Espiral Naranja

Servicio Pesado

Para servicios pesados de succión y descarga, como Riego Agrícola y Construcción Civil.
Temperatura del Trabajo: +5°C ~ +50°C (PVC).



DIÂMETRO NOMINAL	DIÂMETRO INTERIOR	DIÂMETRO EXTERIOR	PRESIÓN DEL TRABAJO		PRESIÓN DEL RUPTURA		VACIO	RADIO DE CURVATURA Trabajo - Mínimo	LARGO
pul.	mm	mm	25°C		25°C		25°C	25°C	m
			kgf/cm ²	lbf/pul ²	kgf/cm ²	lbf/pul ²	mmHg	mm	
5"	127,0	141,5	5,0	71	15,0	213	760	2.550	15 / 30
6"	152,4	169,0	4,6	65	14,0	199	760	2.800	15 / 30

Transparent with Orange Spiral

Heavy Jobs

Recommended for heavy jobs of suction or discharge, such as Agricultural Irrigation and Civil Construction.
Work temperature: +5°C ~ +50°C (PVC).



NOMINAL DIAMETER	INTERNAL DIAMETER	EXTERNAL DIAMETER	WORK PRESSURE		BURST PRESSURE		VACUUM	BEND RADIUS Working - minimum	LENGTH
inches	mm	mm	25°C		25°C		25°C	25°C	m
			kgf/cm ²	psi	kgf/cm ²	psi	mmHg	mm	
5"	127,0	141,5	5,0	71	15,0	213	760	2.550	15 / 30
6"	152,4	169,0	4,6	65	14,0	199	760	2.800	15 / 30